


SHIVELY LABS SAMPLE PATTERN



6813 ANTENNA

VERTICAL RMS: 71.36%


HORIZONTAL RMS: 64.57%

PATTERN NUMBER
FREQUENCY:
ANTENNA AZIMUTH
TOWER
MOUNT STYLE
DISTANCE FROM TOWER
MOUNT REMARKS

6813-029
LOW BAND
0-DEGREES
WORLD 48
LEG MOUNT
STD. MOUNT
N/A

Antennas are supplied with standard mounts
Standard mounts fit 1.25" to 3.50" OD tower legs
or up to a 48-inch face tower
Mounts stand off 17.5-inches
Radomes and Deicers are optional
Pattern studies are optional
Shively Labs recommends anti-rotation brackets
for tower legs under 2-inches

SHIVELY LABS SAMPLE PATTERN



PATTERN NUMBER 6813-029

V-RMS **71.36%**
H-RMS **64.57%**

DEGREE	VERT	HORZ									
0	0.84	1.00	90	0.83	0.58	180	0.12	0.42	270	0.92	0.76
5	0.84	1.00	95	0.77	0.64	185	0.11	0.41	275	0.94	0.69
10	0.84	1.00	100	0.70	0.70	190	0.10	0.40	280	0.96	0.62
15	0.84	0.98	105	0.65	0.72	195	0.10	0.38	285	0.97	0.55
20	0.84	0.96	110	0.59	0.73	200	0.10	0.36	290	0.97	0.48
25	0.84	0.92	115	0.53	0.69	205	0.15	0.33	295	0.96	0.46
30	0.83	0.88	120	0.46	0.64	210	0.20	0.30	300	0.95	0.44
35	0.85	0.84	125	0.41	0.57	215	0.24	0.31	305	0.93	0.49
40	0.86	0.80	130	0.36	0.50	220	0.28	0.32	310	0.91	0.53
45	0.89	0.74	135	0.32	0.43	225	0.34	0.36	315	0.89	0.61
50	0.92	0.67	140	0.27	0.36	230	0.40	0.40	320	0.87	0.68
55	0.94	0.62	145	0.24	0.32	235	0.48	0.51	325	0.87	0.75
60	0.96	0.57	150	0.20	0.28	240	0.56	0.62	330	0.86	0.82
65	0.96	0.50	155	0.17	0.30	245	0.65	0.69	335	0.86	0.87
70	0.96	0.42	160	0.14	0.32	250	0.74	0.76	340	0.85	0.92
75	0.94	0.43	165	0.13	0.35	255	0.80	0.79	345	0.85	0.96
80	0.92	0.44	170	0.12	0.38	260	0.85	0.82	350	0.84	1.00
85	0.88	0.51	175	0.12	0.40	265	0.89	0.79	355	0.84	1.00